


ADAM-6015 ADAM-6017 ADAM-6018

7-ch Isolated RTD Input Modbus TCP Module 8-ch Isolated Analog Input Modbus TCP Module with 2-ch DO 8-ch Isolated Thermocouple Input Modbus TCP Module with 8-ch DO

Vertrieb durch **AMC**
AMC – Analytik & Messtechnik GmbH Chemnitz
 Heinrich-Lorenz-Str. 55 Tel.: +49/371/38388-0
 09120 Chemnitz Fax: +49/371/38388-99
 E-Mail: info@amc-systeme.de Web: www.amc-systeme.de



ADAM-6015 FCC CE RoHS UL US



ADAM-6017 FCC CE RoHS UL US



ADAM-6018 FCC CE RoHS UL US

Specifications

Analog Input

- **Channels** 7 (differential)
- **Input Impedance** > 10 MΩ
- **Input Connections** 2 or 3 wire
- **Input Type** Pt, Balco and Ni RTD
- **RTD Types and Temperature Ranges**
 - Pt 100 -50°C ~ 150°C
 - 0°C ~ 100°C
 - 0°C ~ 200°C
 - 0°C ~ 400°C
 - 200°C ~ 200°C
 - Pt 1000 -40°C ~ 160°C
- Supports both IEC 60751 ITS90 (0.0385 W/W/°C) and JIS C 1604 (0.0392 W/W/°C)
- Balco 500 -30°C ~ 120°C
- Ni 518 -80°C ~ 100°C
- 0°C ~ 100°C
- **Accuracy** ± 0.1 % or better
- High speed mode ±0.5% or better
- **Span Drift** ± 25 ppm/°C
- **Zero Drift** ± 6 μV/°C
- **Resolution** 16-bit
- **Sampling Rate** 10 sample/ second (total)
- High speed mode: 1K sample/second (total)
- CMR @ 50/60 HZ 90dB
- NMR @ 50/60 HZ 60dB
- * high speed mode does not support CMR/NMR
- **Wire Burn-out Detection**

Ordering Information

- **ADAM-6015** 7-ch Isolated RTD Input Modbus TCP Module

Specifications

Analog Input

- **Channels** 8 (differential)
- **Input Impedance** > 10 MΩ (voltage)
- 120 Ω (current)
- **Input Type** mV, V, mA
- **Input Range**
 - ±150mV, ±500mV, ±1 V,
 - ±5V, ±10V, 0 ~ 150mV, 0
 - ~ 500mV, 0 ~ 1V, 0 ~ 5V
 - , 0 ~ 10V, 0 ~ 20mA, 4 ~
 - 20mA, ±20mA
- **Accuracy** ±0.1% (voltage)
- ±0.2% (current)
- **Span Drift** ±25 ppm/°C
- **Zero Drift** ±6 μV/°C
- **Resolution** 16-bit
- **Sampling Rate** 10 or 100 sample/ second (total)
- CMR @ 50/60 HZ 90dB
- NMR @ 50/60 HZ 67dB
- **Common-Mode Voltage** 350V_{DC}
- **Digital Output**
- **Channels** 2, open collector to 30 V,
- 100 mA max. load
- **Power Dissipation** 300 mW for each module
- **Output Delay** On: 100μs
- Off: 150μs

Ordering Information

- **ADAM-6017** 8-ch Isolated AI with 2-ch DO Modbus TCP Module

Specifications

Analog Input

- **Channels** 8 (differential)
 - **Input Impedance** > 10 MΩ
 - **Input Type** Thermocouple
 - **Thermocouple Type and Range:**
- | | | | |
|----------|--------------|----------|---------------|
| J | 0 ~ 760°C | R | 500 ~ 1,750°C |
| K | 0 ~ 1,370°C | S | 500 ~ 1,750°C |
| T | -100 ~ 400°C | B | 500 ~ 1,800°C |
| E | 0 ~ 1,000°C | | |
- **Accuracy** ±0.1%
 - **Span Drift** ±25 ppm/°C
 - **Zero Drift** ±6 μV/°C
 - **Resolution** 16-bit
 - **Sampling Rate** 10 sample/ second (total)
 - CMR @ 50/60 HZ 90dB
 - NMR @ 50/60 HZ 60dB
 - **Wire Burn-out Detection**

Digital Output

- **Channels** 8, open collector to 30 V,
- 100 mA max. load
- **Power Dissipation** 300 mW for each module

Ordering Information

- **ADAM-6018** 8-ch Isolated Thermocouple Input Modbus TCP Module w/ 8-ch DO



Common Specifications

General

- **LAN** 10/100Base-T(X)
- **Power Consumption** 2.5 W @ 24 V_{DC} (ADAM-6015)
- 2.7 W @ 24 V_{DC} (ADAM-6017)
- 2 W @ 24 V_{DC} (ADAM-6018)
- **Connectors** 1 x RJ-45 (LAN), Plug-in screw terminal block (I/O and power)
- **Watchdog** System (1.6 second) and Communication (programmable)

- **Power Input** 10 ~ 30 V_{DC}
- **Supports Peer-to-Peer**
- **Supports GCL**
- **Supports Modbus/TCP, TCP/IP, UDP, HTTP and MQTT (ADAM-6017) Protocols**
- **Protection**
- **Over Voltage Protection** ±35 V_{DC}
- **Isolation Protection** 2,000 V_{DC}
- **Built-in TVS/ESD Protection**
- **Power Reversal Protection**

Environment

- **Operating Temperature** -10 ~ 70°C (14 ~ 158°F)
- 20 ~ 70°C (-4 ~ 158°F) (ADAM-6017)
- **Storage Temperature** -20 ~ 80°C (-4 ~ 176°F)
- 30 ~ 80°C (-22 ~ 176°F) (ADAM-6017)
- **Operating Humidity** 20 ~ 95% RH (non-condensing)
- **Storage Humidity** 0 ~ 95% RH (non-condensing)