

APAX-5430 APAX-5435

SATA SSD module

mPCIe module to support iDoor

NEW



APAX-5430



Specifications

General

- **Certification** CE, FCC class A
- **Dimensions (W x H x D)** 30 x 139 x 100 mm
- **Enclosure** ABS+PC
- **Weight** 165 g
- **Power Consumption** 2.5 W @ 24 V_{DC} (typical)

Function

- **Interface** SATA
- **RAID** Supports RAID 0/1
- **Power Supply** 5V:2A
3.3V:2A
- **Support SATA I/II/III 2.5" SSD (HDD is not recommended)**
- **Support Hot swap**

Environment

- **Operating Temperature** -10 ~ 60°C (when mounted vertically)
- **Storage Temperature** -40 ~ 70°C
- **Relative Humidity** 5 ~ 95% (non-condensing)

Ordering Information

- **APAX-5430** SATA SSD Module

Note: APAX-5430 can only be used by controllers with a PCI Express interface (ex. APAX-5580)

Vertrieb durch



AMC – Analytik & Messtechnik GmbH Chemnitz

Heinrich-Lorenz-Str. 55 Tel.: +49/371/38388-0
09120 Chemnitz Fax: +49/371/38388-99
E-Mail: info@amc-systeme.de Web: www.amc-systeme.de

NEW



APAX-5435



Specifications

General

- **Certification** CE, FCC class A
- **Dimensions (W x H x D)** 30 x 139 x 100 mm
- **Enclosure** ABS+PC
- **Weight** 165 g
- **Power Consumption** 0.5 W @ 24 V_{DC} (typical)

Function

- **Interface** mini PCI express 2.0 (support Advantech iDoor)
mSATA (support t SATA GENI/GENII/GENIII)
- **Support Hot Plug**

Environment

- **Operating Temperature** -10 ~ 60°C (when mounted vertically)
- **Storage Temperature** -40 ~ 70°C
- **Relative Humidity** 5 ~ 95% (non-condensing)

Supported iDoor Modules

- **PCM-26D2CA** SJA1000 CANBUS, CANopen, DB9
- **PCM-26D1DB** 1-Port Hilscher netX100 FieldBus mPCIe, ProfiBus, DB9
- **PCM-26R2PN** 2-Port Hilscher netX100 FieldBus mPCIe, PROFINET, RJ45
- **PCM-26R2EC** 2-Port Hilscher netX100 FieldBus mPCIe, EtherCAT, RJ45
- **PCM-26R2EI** 2-Port Hilscher netX100 FieldBus mPCIe, EtherNet/IP, RJ45
- **PCM-24S2WF** Wi-Fi 802.11 a/b/g/n 2T2R w/ Bluetooth 4.0, Half-size mPCIe, 2-port SMA
- **PCM-24S33G** Wide-Temp 3.75G HSPA and GPS, 2-in-1, Full-size mPCIe w/ dual SIM Card holder, Antenna, cable
- **PCM-24R2GL** 2-port GbE BaseT(X) 10/100/1000 Mbps, mPCIe Card
- **PCM-24R1TP** Intel® 82574L, GbE, RJ45 x 1
- **PCM-23U1DG** USB Slot w/ Lock for USB Dongle, Half-size mPCIe
- **PCM-2300MR** MRAM, 2 MByte

Ordering Information

- **APAX-5435** mPCIe Module to support iDoor

Note: APAX-5435 can only be used by controllers with a PCI Express interface (ex. APAX-5580)