

Advantech Control Cabinet PC

Designed for Machine Construction and Plant Engineering Applications



- / Introduction
- / Product Features
- / Intelligent Software
- / Selection Guide




Advantech Control Cabinet PC

Wide Range of Product Form-factors for Different Mounting Scenarios of Cabinet Applications


Advantech's UNO-1000/3000 series of Embedded Control Cabinet PCs are fanless with high performance, multiple extensions, and ruggedized chassis. With iDoor Technology which supports automation feature extensions such as Fieldbus communication, Wi-Fi/3G, Digital I/O and POE. Versatile Mounting space DIN-Rail Mount, Wall Mount, Enclosure Mount and Panel mount with easy installation indicated market segments. In terms of the type of mounting, with their Control Cabinet PC, they are suitable for IoT gateway, motion and vision applications.

Features & Benefits



Dual Power Input

Dual power input with wide range operating voltage is a fail-safe mechanism to reduce working unit maintaining down time by alternative power input source. And remote power on assists working units go back online from outside of the cabinet.



Multiple Expansion

UNO supports latest range of expansion interfaces including PCIe for high density I/O, iDoor for fieldbus modules, PCI for motion cards with easy installation captive thumb screws.



Dual iDoor Expansion

Advantech's iDoor technology provides simple, flexible, and reliable expansion in high density systems using versatile color identification and multiple functions.



Built-in Digital I/O

Built-in DI/DO for simple I/O control, status detection, lighting control and event triggering in order to save extra cost and devices.



Dual Digital Display

Flexible display options provide resolutions of up to 4K/2K and provide excellent image quality.



Enclosure Mount (UNO-3400)

Compact outside heatsink mounts through a corresponding cut-out in the cabinet or enclosure panel which integrated seals represent high performance as IP67.



IEC-61010 certified

UNO-3382G/ 3384G are evaluated to the UL/ IEC-61010 standard and support book mounting methods which makes them suitable for installing in harsh industrial environments.



Easy Maintenance



Captive Thumb Screw

Operators can work efficiently with captive thumb screws as a superior tool to strengthen swapping HDD, CFast & PCI/PClant for maintaining storage and expansion devices.



Hot-swap RTC Battery

Removable RTC battery saves time and cost by avoiding disassembling the working unit and shutting down the whole operation.



Hot-swap

Hot-swap HDD deploy software control data easily in working units without power off.

Intelligent Software

Advantech WebAccess is a 100% web-based SCADA (Supervisory Control And Data Acquisition) software and it acts as an IIoT Platform providing open interfaces for partners to develop IoT applications for different vertical markets. In addition to traditional SCADA functions, WebAccess has an intelligent dashboard, to provide users with cross-platform, cross-browser data analysis and user interface using HTML5 technology. As well as the built-in widgets, WebAccess also provides Widget Builder to allow customers to build their own.

WebAccess/SCADA

WebAccess/HMI

WebAccess/HMI Designer is powerful yet intuitive software to create total solutions for HMI (Human Machine Interface) products. WebAccess/HMI Designer is proven in many application fields and is an easily integrated development tool. WebAccess/HMI Runtime, a part of WebAccess/HMI, guarantees reliability and performance of open platform because of the minimum system overhead, high communication data rates, sub-second screen switching, and 24/7 operation.

Remote Device Management

WISE-PaaS/RMM is an innovative remote management and cloud-based software preloaded in all Advantech embedded solutions, allowing the efficient and centralized remote monitoring and management of embedded devices in real-time, device health status, system configuration, system protection, and recovery & backup. WISE-PaaS/RMM targets the needs of creating a more intelligent and interconnected embedded computing solution.

WISE-PaaS/RMM



System Protection

Versatile Mounting with Easy Installation



DIN-Rail Mount

UNO-1000 series can be painlessly installed on the rail with the sophisticated din-rail kit at the rear and R-angle design at the front.



Wall Mount

Easy pull-out operation is extremely convenient that advantage is suitable for all but the heavier installations.



Book Mount

The UNO-3300 offers an open and universal automation solution, saves space and allows quick installation in a control cabinet.



Enclosure Mount

The UNO-3400 series are designed for easier and quick installation in control cabinets. As UNO-3400 which has the Placing-and-Click snap connector which has further considered users' activity and then simplifies the installation procedures.

Capable Storage

/SSD let operators store data or collect easily when maintaining without interruptions.

Selection Guide

Vertrieb durch



AMC – Analytik & Messtechnik GmbH Chemnitz

Heinrich-Lorenz-Str. 55 Tel.: +49/371/38388-0
09120 Chemnitz Fax: +49/371/38388-99
E-Mail: info@amc-systeme.de Web: www.amc-systeme.de



Model Name	UNO-1251G	UNO-1372G-J	UNO-1372G	UNO-1483G	UNO-3272G	UNO-3283G/3285G	UNO-3382G/3384G	UNO-3483G
CPU	ARM Cortex A8, 600MHz	Intel® Celeron® J1900	Intel® Atom™ E3845 1.91GHz	Intel® Core™ i3-4010U 1.7GHz	Intel® Celeron® J1900	Intel® Core™ i7-6822EQ 2.0GHz Intel® Core™ i5-6442EQ 1.9GHz Intel® Core™ i5-6440EQ 1.9GHz Intel® Core™ i3-6102E 1.9GHz	Intel® Core™ i7-4650U 1.7Hz	Intel® Core™ i7-3612QE
Onboard RAM	256MB DDR2 SDRAM	4GB DDR3L SO-DIMM	4GB DDR3L SO-DIMM	8GB DDR3L SO-DIMM	4GB DDR3L SO-DIMM	8GB DDR4 SO-DIMM	8GB DDR3L SO-DIMM	8GB DDR3L SO-DIMM
Display	-	HDMI, DP	HDMI, VGA	DP, VGA	VGA, HDMI	DVI-I, HDMI	HDMI, DP	VGA, HDMI
Audio	-	-	Line-out	Line-out	Line-out	Mic in, Line out (pin header)	N/A (built-in Line-in/out/Mic,I/O through iDoor)	Mic in, Line out (pin header)
Serial Ports	1 x RS-232, 1x RS-422/485, 1 x RS-485	4 x RS-232/ 422/485	1 x RS-232, 1 x RS-422/485	1 x RS-232, 2 x RS-422/485	2 x RS-232, 2 x RS-232/422/485	2 x RS-232/422/485, 2 x RS-232 (pin header)	1 x RS-232/422/485	1 x RS-232, 1 x RS-422/485 (pin header)
Ethernet Ports	2 x 10/100 Mbps Base-T	2 x 10/100/1000 Mbps Base-T	3 x 10/100/1000 Mbps Base-T	4 x 10/100/1000 Mbps Base-T	2 x 10/100/1000 Mbps Base-T	2 x 10/100/1000 Mbps Base-T	2 x 10/100/1000 Mbps Base-T	2 x 10/100/1000 Mbps Base-T
USB Ports	1 x USB 2.0	3 x USB 2.0 1 x USB 3.0	2 x USB 2.0 1 x USB 3.0	2 x USB 2.0 2 x USB 3.0	3 x USB 2.0 1 x USB 3.0	6 x USB3.0	2 x USB 2.0 2 x USB 3.0	2 x USB 2.0 2 x USB 3.0
PCIe/PCI Expansion	1 x Mini PCIe	2 x Mini PCIe	2 x Mini PCIe	1 x PCIe x 1 2 x Mini PCIe	2 x PCIe1 1 x Mini PCIe	UNO-3283G: 1 x PCIe16+ 1 x PCI, 2 x Mini PCIe UNO-3285G: 2 x PCIe8+ 2 x PCI, 2 Mini PCIe	UNO-3382G: 2 x Mini PCIe UNO-3384G: 2 x MiniPCIe, 1 x PCI + 1 x PCIe 4	1 x PCIe 4, 3 x Mini PCIe
Digital I/O	-	4-ch DI, 4-ch DO	4-ch DI, 4-ch DO	4-ch DI, 4-ch DO	4-ch DI, 4-ch DO (optional)	-	-	-
Micro SD	1 x 1G MicroSD card 1 x MicroSD card slot	-	-	-	-	-	-	-
CFast Slots	-	-	-	-	-	CFast x 1	CFast x 1	-
2.5" HDD Expansion slot	-	1 x SATA HDD	2 x SATA HDD, support RAID 0/1	2 x SATA HDD, support RAID 0/1	2 x SATA HDD, support RAID 0/1			
Operating Systems	Windows Embedded Compact7(WEC7), Embedded Linux	Win7/8/10, WES7, Win10 Ent. LTSC, AdvLinux	Win7/8/10, WES7, Win10 Ent. LTSC, AdvLinux	Win7/8, WES7, AdvLinux				
Mounting	DIN-rail Mount	DIN-rail Mount	DIN-rail/Wall Mount	DIN-rail/Wall Mount	Wall, Stand Mount	Wall, Stand, Enclosure Mount	Book Mount	Enclosure Mount
Power Input Range	10-36V _{DC}	9-36V _{DC}	10-36V _{DC}	12/24V _{DC} ± 20%	10-36V _{DC}	10-36V _{DC}	24V _{DC} ± 20%	12/24V _{DC} ± 20%
Operating Temperature	-20 ~ 60°C (-4 ~ 140°F)	-20 ~ 60°C (-4 ~ 140°F)	-20 ~ 60°C (-4 ~ 140°F)	-20 ~ 60°C (-4 ~ 140°F)	-20 ~ 60°C (-4 ~ 140°F)	-20 ~ 60°C (-4 ~ 140°F)	0 ~ 55°C (32 ~ 131°F)	-20 ~ 60°C (-4 ~ 140°F)
Power Consumption Typical	5.3W	19W	24W	41W	24W	90W	45W	50W
Dimensions (W x D x H)	50 x 90 x 100 mm	65 x 105 x 150mm	85 x 139 x 152 mm	106 x 139 x 198 mm	145 x 177 x 238 mm	UNO-3283G: 142 x 238 x 117 mm UNO-3285G: 182 x 238 x 177 mm	UNO-3382G: 65.2 x 254 x 207mm UNO-3384G: 103.2 x 254 x 207mm	305 x 82 x 225 mm

Advantech iDoor Module

Memory/Storage/External I/O Communication FieldBus Digital / Analog I/O

PCM-2300MR MR4A16B, MRAM, 2MByte	TPM Compliant with TCG 1.2	PCM-23C1CF CFast, Ejection Type I, CFast x 1	PCM-23U1DG Locked USB Slot for USB Dongle, USB x 1
PCM-24D2R2/24D2R4 OXPCle-952 UART, Isolated RS-232, 422/485, DB9 x 2	OXPCle-954 UART, Non-Isolated RS-232, 422/485, DB37 x 1	PCM-24R2PE Intel i350, GbE, PoE IEEE 802.3af, PD, RJ45 x 2	PCM-24R2GL Intel i350 PCIe, GbE, LAN Mini Card, RJ45 x 2
PCM-24R1TP Intel 82574L, GbE, IEEE 1588 PTP, RJ45 x 1	USB 3.0 Mini Card, USB x 2	PCM-24S2WF 802.11 a/b/g/n 2T2R w/ BT4.0, Atheros AR9462, SMA x 2	PCM-24S23G 6-band HSPA Cellular Module, SIM Holder+ GPS, SMA x 2
PCM-24S24G LTE Bands, UMTS/HSPA Bands, GPS/GPRS Bands, SMA x 2	SJA1000 CANBus, CANOpen, DB9 x 2	PCM-26D1PB Hilscher netX100 FieldBus, ProfiBus, DB9 x 1	PCM-27D24DI Digital I/O, 16 DI / 8 DO, Isolation, DB37 x 1