
# PCM-24R1TP-BE Intel I225, 2.5Gb/s, IEEE 1588, TSN, R.I45 x 1



### **Features**

- · Meets Advantech iDoor technology standard
- Supports Time Sensitive Network (TSN) (IEEE 1588/802.1AS Rev, 802.1Qav, 802.1Qbv)
- Support PXE
- High speed Ethernet supports 10BASE-Te, 100BASE-TX, 1000BASE-T and 2500BASE-T 802.3
- Achieves time synchronization for device or system
- Real-time Ethernet with hardware based precision time protocol



## Introduction

PCM-24R1TP-BE supports TSN (Time Sensitive Network) which is an update to the IEEE Ethernet standard intended to address the needs of control systems with standard Ethernet technology. This includes standard time synchronization and deterministic network communication over standard Ethernet, allowing operations networks to leverage the advantages of traditional Ethernet while meeting the timing and control needs of control and measurement applications.

PCM-24R1TP-BE features on supporting TSN that can be used in Audio/Video Bridging (AVB) applications and industrial applications that require TSN capabilities. This is a flexible design that enables customers to customize their features with iDoor Technology.

## **Specifications**

#### General

Bus Type PCI Express Mini Card Revision 1.2

Certification CE, FCC class A

Connectors 1 x RJ45 GbE Half-/Full-Duplex

Dimensions Module: 51 x 30 x 12.4 mm (2" x 1.18" x 0.49") I/O Plate: 81 x 19.4 x 41 mm (3.19" x 0.76" x 1.61")

 Power Consumption Typical: +3.3V @ 9 W

#### **Communications**

 LAN Controller Intel 1225 Ethernet Chip

Speed 10/100/000BASE-TX, Auto-negotiation

Support **IEEE 1588** 

#### **Protection**

 Isolation Protection 1,500 V<sub>DC</sub>

 ESD Protection 4KV (Contact), 8KV (Air)

1,000 V EFT Protection Surge Protection 1,000 V<sub>DC</sub>


#### Software

 OS Support Microsoft® Windows® 10, Linux Ubuntu 18.04

#### **Environment**

• Humidity (Operating) 95% RH @40 °C, non-condensing • Operating Temperature  $-20 \sim 60^{\circ}\text{C} (-4 \sim 140^{\circ}\text{F})$ • Storage Temperature  $-40 \sim 85^{\circ}\text{C} \ (-40 \sim 185^{\circ}\text{F})$ 

## **Dimensions**



## **Ordering Information**

■ PCM-24R1TP-BE Intel I225, 2.5Gb/s, IEEE 1588, TSN, RJ45 x 1



Last undated: 10-Mar-2023



ADVANTECH (Automation



