


# WISE-4210

## Industrial Proprietary LPWAN (SUB-G) Wireless I/O Module



### Features

- Proprietary LPWAN with using sub-1GHz wireless frequency
- Battery power for 5 years with 3 x 3.6V AA batteries
- Up to 5 km communication range in open space
- Longer communication range than 2.4GHz
- Better penetration through concrete and steel than 2.4GHz
- Less interference than 2.4GHz spectrum
- Application-ready I/O combination with modularization design



ADVANTECH iAutomation  
Premier Partner

### Introduction

LPWAN, created for machine-to-machine (M2M) and Internet of things (IoT) networks, is not a single technology, but a variety of low-power, wide area network technologies. Compared with traditional mobile network, LPWAN is known as lower cost with higher power efficiency. WISE-4210 series is the proprietary LPWAN which provides better connection compare with traditional 2.4G WiFi, WISE-4210 series is helpful of eliminating network interference.

Additionally, WISE-4210 utilize a LPWAN(low-power, wide-area networks) wireless interface, which has a kilometer-long communication distance and battery power. The features of LPWAN make WISE modules ideal solutions for energy and environment monitoring.

### Reduced Interference and Extended Communication Range

Compared with Wi-Fi, Bluetooth, Zigbee, or other 2.4GHz wireless interfae, a sub-GHz interface can reduce interference at sites. Moreover, Sub-GHz is a type of LPWAN designed for long-range communications. Under the same power consumption, sub-GHz offers a longer communication range with low data rate than other 2.4 GHz. technologies.

### Powered by a 3.6V AA Lithium Battery

The low power consumption of sub-GHz enables the sensor node to be powered by a battery. With a 3.6V AA Lithium battery, the sensor node can maintain communication at a distance of 5 km for up to 5 years, thereby eliminating the need to recharge or change batteries.



### Star Topology


Star topology, also known as star network, is the most common network setup. In star topology, every node connects to a central network device which means WISE-4210-S200 series nodes acts as clients should be connected with WISE-4210-AP. In this configuration, user can organize their own network with 64 nodes paired. Data on a star network pass through WISE-4210-AP before continuing to its destination. WISE-4210-AP with a LAN cable manages and controls most of all functions of the network.

### MQTT and RESTful API IoT Protocol Support

IoT Wireless sensor nodes are designed for not only automation applications but also IoT applications that may use MQTT or RESTful web API IoT protocols for cloud integrations.

### Azure IoT Hub Support

To provide a complete IoT sensing solution, the WISE-4210 series goes beyond being a wireless communication interface for sensors—it also provides cloud connectivity for additional user applications. With support for HTTPS and integrated APIs for Azure IoT Hub, the WISE-4210 series can automatically push data to the cloud without requiring an IoT gateway.



Vertrieb durch **AMC**  
**AMC – Analytik & Messtechnik GmbH Chemnitz**  
Heinrich-Lorenz-Str. 55 Tel.: +49/371/38388-0  
09120 Chemnitz Fax: +49/371/38388-99  
E-Mail: info@amc-systeme.de Web: www.amc-systeme.de

## Common Specification

### WISE-4210

▪ Frequency Band	NA915: 923MHz (920.60-924.60), BW: 400kHz EU868: 868MHz (865.00-869.00), BW: 400kHz UN433: 433MHz (433.05-434.55), BW: 300kHz 902-928MHz: 1.33 dBi 863-870MHz: 2.19 dBi
▪ Antenna Gain	625bps, 50kbps
▪ Data Rate	625bps: 5 km with line of sight
▪ Outdoor Range	50kbps: 2 km with line of sight
▪ Topology	Star
▪ Network Capacity	64 clients

### General

▪ Power Input	AP: 10 ~ 50 V <sub>DC</sub> Sensor Node: 3 x AA, 3.6V Lithium Battery or 10 ~ 50 V <sub>DC</sub>
▪ Battery Life	625bps: 5 years with 10 minute update rate @ 25°C 50kbps: 5 years with 1 minute update rate @ 25°C
▪ Configuration Interface	AP: LAN port Sensor Node: Micro-B USB
▪ LED Indicator	Status, Error, Tx, Rx, Battery/Signal Level
▪ Mounting	DIN 35 rail, wall, pole and stack
▪ Dimension (W x H x D)	70 x 102 x 38 mm
▪ Certification	CE, FCC, IC, NCC, TELEC

### Environment

▪ Operating Temperature	-25 ~ 70°C
▪ Operating Humidity	5 ~ 95% RH
▪ Storage Temperature	-40 ~ 85°C
▪ Storage Humidity	0 ~ 95% RH

### WISE-4210-AP (Access Point)

▪ Data Rate	625 bps, 2.5k bps, 5k bps, 50k bps.
▪ Ethernet	RJ-45 (for configuration and data query)
▪ RS-485	Data+, Data- (for query node data)
▪ Messaging Protocol	Modbus/TCP, Modbus/RTU, REST, MQTT
▪ Application Protocol	HTTP, HTTPS, SNMP, DHCP
▪ Transport Protocol	TCP, UDP
▪ Supports RESTful Web API in JSON format	
▪ Supports Web Server in HTML5	

### WISE-4210-S231 (Built-in Temperature & Humidity Sensor)

#### Temperature Sensor

▪ Operating Range	-25°C ~ 70°C (-13°F ~ 157.9°F)
▪ Resolution	0.1 (°C/°F/K)
▪ Accuracy	±1.0°C (±1.8°F) (vertical installation)

#### Humidity Sensor

▪ Operating Range	10 ~ 90% RH
▪ Resolution	0.1% RH
▪ Accuracy	±4% RH @ for 0%-50% RH ±6% RH @ 50%-60% RH ±10% RH @ 60%-90% RH

### WISE-S214 (4AI/4DI)

#### Analog Input

▪ Channels	4
▪ Resolution	16bits Bipolar 15bits Unipolar
▪ Sampling Rate	1Hz (per Channel) with 50/60Hz Rejection (Power Saving Mode)
▪ Accuracy	10Hz (Total) with 50/60Hz Rejection (Normal Mode) ±0.1% for Voltage Input ±0.2% for Current Input
▪ Input Range	0-150mV, 0-500mV, 0-1V, 0-5V, 0-10V, ±150mV, ±500mV, ±1V, ±5V, ±10V, 0-20mA, ±20mA, 4-20mA
▪ Input Impedance	>1MΩ (Voltage)
▪ Isolated voltage	3kVrms
▪ Support Data Scaling and Averaging	

#### Digital Input

▪ Channels	4 (Dry Contact)
▪ Supports 32-bit counter input function (maximum signal frequency 200Hz)	
▪ Supports keep/discard counter value on power-off	
▪ Support inverted digital input status	

### WISE-S250 (6DI, 2DO & 1RS-485)

#### Digital Input

▪ Channels	6 (Dry Contact)
▪ Supports	3kHz Frequency Input

#### Digital Output (Sink Type)

▪ Channels	2
▪ Output Current	100 mA
	At 0 -> 1: 100 us
	At 1 -> 0: 100 us
	(for Resistive Load)
▪ Supports Pules Output	5 kHz
▪ Max. Load Voltage	30V

#### Serial Port

▪ Port Number	1
▪ Type	RS-485
▪ Data Bits	7, 8
▪ Stop Bits	1, 2
▪ Parity	None, Odd, Even
▪ Baud Rate (bps)	1200, 2400, 4800, 9600, 19200, 38400, 57600, 115200
▪ Protocol	Modbus/RTU (Total 64 addresses by 30 max. instructions)

### WISE-S251 (6DI/1RS-485)

#### Digital Input

▪ Channels	6 (Dry Contact)
▪ Supports 32-bit counter input function (maximum signal frequency 200Hz)	
▪ Supports keep/discard counter value on power-off	
▪ Support inverted digital input status	

#### Serial Port

▪ Port Number	1
▪ Type	RS-485
▪ Data Bits	7, 8
▪ Stop Bits	1, 2
▪ Parity	None, Odd, Even
▪ Baud Rate (bps)	1200, 2400, 4800, 9600, 19200, 38400, 57600, 115200
▪ Protocol	Modbus/RTU (Total 32 address by max. 8 instructions)

## Ordering Information

### WISE-4210 Access Point

▪ WISE-4210-APNA	LPWAN Wireless to Ethernet AP – NA915/EU868
▪ WISE-4210-APUA	LPWAN Wireless to Ethernet AP – UN433

### WISE-4210 Node

▪ WISE-4210-NA	Proprietary LPWAN SUB-G Wireless I/O Module – NA915/EU868
▪ WISE-4210-UA	Proprietary LPWAN SUB-G Wireless I/O Module – UN433
▪ WISE-4210-S231-NA	LPWAN IoT WSN Temp & RH Sensor- NA902/EU868
▪ WISE-4210-S231-UA	LPWAN IoT WSN Temp & RH Sensor - UN433

### WISE-S200 I/O Module

▪ WISE-S214-A	4AI/4DI
▪ WISE-S250-A	6DI, 2DO & 1RS-485
▪ WISE-S251-A	6DI & 1RS-485

\* Power saving is not for downlink mode.

### Accessories

▪ 1760002647-01	Bat.Cylindrical 3.6V/2500mAh AA Li/SOCI2
▪ 1750008836-01*	863-870MHz Dipole Antenna for WISE-4210
▪ 1750008837-01*	902-928MHz Dipole Antenna for WISE-4210

\* AS923/EU868 version of WISE-4210 needs to order antenna separately

